

## XVD Vandal Resistant Dome with Built-in LEDs



	XVD35V8CMHR-LED	XVD35V8CM-LED	XVD43CM-LED
<b>Horizontal Resolution</b>	530 TV Lines	420 TV Lines	420 TV Lines
<b>Pick up Device</b>	1/3" INTERLINE transfer CCD		
<b>Total Pixels</b>	PAL:795(H) x 596(V)	PAL:537(H) x 597(V)	
<b>Effective Pixels</b>	PAL:752(H) x 582(V)	PAL:500(H) x 582(V)	
<b>Sync. system</b>	2 1 Internal		
<b>Scanning system</b>	PAL :625 lines / 50 Fields		
<b>Video Output</b>	1.0 Vp-p / 75 ohm composite		
<b>IR Cut Filter</b>	Nil		
<b>Electronic Shutter</b>	Auto 1/50~1/100,000 sec.		
<b>Lens</b>	Vari Focal Lens : 3.5 mm -8 mm		Standard: 4.3mm
<b>S/N Ratio</b>	More than 48dB (AGC OFF)		
<b>Min. Illumination</b>	0.5 Lux colour/ F2.0	0.3 Lux colour/ F2.0	0.4 Lux colour/ F2.0
<b>IR Distance</b>	20m (28pcs IR LED)	20m (28pcs IR LED)	10m (14pcs IR LED)
<b>IR Trigger</b>	3.1 Lux / 3.7 Lux IR ON / OFF		2.6 Lux / 2.7 Lux IR ON / OFF
<b>Power Supply</b>	DC 12V		
<b>Power Consumption</b>	6.2W (Max)	5.9W (Max)	3.5W (Max)
<b>Current</b>	520mA (Max)	490mA (Max)	290mA (Max)
<b>Dimension</b>	82.5mm (H) x 119mm (Dia)		69mm (H) x 94mm (Dia)
<b>Operating Temp</b>	-10 to 50°C (14 to 122°F)		
<b>Storage Temp</b>	-20 to 70°C (-4 to 158 °F)		

- 1/3" Colour CCD
- 530TVL or 420TVL Resolution
- Vandal Resistant Casing
- Up to 20m Illumination with 28 LEDs
- 3.5-8mm Varifocal and 4.3mm Lens Options
- Easy P/T Adjustment